

# CRUISER 15W-40

Diesel engine oil

## Description

**CRUISER 15W-40** is high performance lubricant designed to stay ahead of the latest developments in diesel engine technology that require overall protection especially against wear and corrosion, engine cleanliness and reduced fuel consumption with special base neutralizer additives to neutralize the acids that are formed within the engine. **CRUISER 15W-40** is a multigrade lubricant providing perfect lubrication for both high and low temperature operation.

## Application

**CRUISER 15W-40** is suitable for use in high power diesel engine fitted with turbo chargers generally used in transport, heavy equipment and industrial applications. The lubricant can also be used for gasoline engines.

## Specification Meets

**CRUISER 15W-40** meet API Service CF-4/SG, ACEA E2-96, MB Sheet 228.1, MTU Type 1, and MAN 271 specifications.

## Typical Data of CRUISER 15W-40

Characteristics	Unit	CRUISER 15W-40	Test Method
Color		L 1.5	ASTM D 1500
Density @ 15 °C	kg/L	0.8768	ASTM D 4052
Kinematic Viscosity @ 40 °C	cSt	117.70	ASTM D 445
Kinematic Viscosity @ 100 °C		15.55	
Viscosity Index		139	ASTM D 2270
Flash Point (COC)	°C	238	ASTM D 92
Pour Point	°C	-27	ASTM D 97
CCS Viscosity @ 20 °C	cP	5526	ASTM D 5293
Total Base Number	mg KOH/g	10.480	ASTM D 2896

\* the typical characteristic mentioned represent mean values